Pari Vlasta

Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012. Date of issue: 05/28/2014 Revision date: 05/28/2014 Version: 1.0

SECTION 1: Identification of the s	
	ubstance/mixture and of the company/undertaking
1.1. Product identifier	
Product name	: STARTING FLUID
Product code	: 0797
1.2. Relevant identified uses of the su	ubstance or mixture and uses advised against
Use of the substance/mixture	: Starting Fluid.
1.3. Details of the supplier of the safe	ety data sheet
The Penray Companies, Inc. 440 Denniston Ct. Wheeling, IL 60090 T (800) 373-6729	
Manufactured For: Aftermarket Auto Parts Alliance San Antonio, TX 78258 210-492-4868 www.alliance1.com	
1.4. Emergency telephone number	
Emergency number	: 210-492-4868 CHEMTREC (800) 424-9300 CHEMTREC International +1 (703) 527-3887 24 hr
SECTION 2: Hazards identification	1
2.1. Classification of the substance of	or mixture
GHS-US classification Flammable Aerosol 1	
Flammable Aerosol 1 Gases Under Pressure - Compressed Gas Skin irritation 2 Carcinogenicity 2 Specific target organ toxicity - Single exposur Aspiration hazard 1	re 3
Flammable Aerosol 1 Gases Under Pressure - Compressed Gas Skin irritation 2 Carcinogenicity 2 Specific target organ toxicity - Single exposur	re 3
Flammable Aerosol 1 Gases Under Pressure - Compressed Gas Skin irritation 2 Carcinogenicity 2 Specific target organ toxicity - Single exposur Aspiration hazard 1 2.2. Label elements GHS-US labelling	re 3
Flammable Aerosol 1 Gases Under Pressure - Compressed Gas Skin irritation 2 Carcinogenicity 2 Specific target organ toxicity - Single exposur Aspiration hazard 1 2.2. Label elements GHS-US labelling Hazard pictograms (GHS-US)	$: \underbrace{_{HS02}}_{GHS02} \underbrace{_{GHS04}}_{GHS04} \underbrace{_{GHS07}}_{GHS07} \underbrace{_{GHS08}}_{GHS08}$
Flammable Aerosol 1 Gases Under Pressure - Compressed Gas Skin irritation 2 Carcinogenicity 2 Specific target organ toxicity - Single exposur Aspiration hazard 1 2.2. Label elements GHS-US labelling Hazard pictograms (GHS-US) Signal word (GHS-US)	: K = K = K = K = K = K = K = K = K = K =
Flammable Aerosol 1 Gases Under Pressure - Compressed Gas Skin irritation 2 Carcinogenicity 2 Specific target organ toxicity - Single exposur Aspiration hazard 1 2.2. Label elements GHS-US labelling Hazard pictograms (GHS-US)	$: \underbrace{_{HS02}}_{GHS02} \underbrace{_{GHS04}}_{GHS04} \underbrace{_{GHS07}}_{GHS07} \underbrace{_{GHS08}}_{GHS08}$
Flammable Aerosol 1 Gases Under Pressure - Compressed Gas Skin irritation 2 Carcinogenicity 2 Specific target organ toxicity - Single exposur Aspiration hazard 1 2.2. Label elements GHS-US labelling Hazard pictograms (GHS-US) Signal word (GHS-US)	: CHS02 CHS02 CHS04 CHS07 CHS07 CHS08
Flammable Aerosol 1 Gases Under Pressure - Compressed Gas Skin irritation 2 Carcinogenicity 2 Specific target organ toxicity - Single exposur Aspiration hazard 1 2.2. Label elements GHS-US labelling Hazard pictograms (GHS-US) Signal word (GHS-US) Hazard statements (GHS-US)	 : With the second sec
Flammable Aerosol 1 Gases Under Pressure - Compressed Gas Skin irritation 2 Carcinogenicity 2 Specific target organ toxicity - Single exposur Aspiration hazard 1 2.2. Label elements GHS-US labelling Hazard pictograms (GHS-US) Signal word (GHS-US) Hazard statements (GHS-US) Precautionary statements (GHS-US)	 : With the second sec
Flammable Aerosol 1 Gases Under Pressure - Compressed Gas Skin irritation 2 Carcinogenicity 2 Specific target organ toxicity - Single exposur Aspiration hazard 1 2.2. Label elements GHS-US labelling Hazard pictograms (GHS-US) Signal word (GHS-US) Hazard statements (GHS-US) Precautionary statements (GHS-US) 2.3. Other hazards	 With the second s

EN (English)



Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 3: Composition/information on ingredients

Substance 3.1.

Not applicable

Name	Product identifier	%	GHS-US classification
Heptane, branched, cyclic and linear	(CAS No) 426260-76-6	60 - 100	Flam. Liq. 2 Skin Irrit. 2 STOT SE 3 Asp. Tox. 1
Ethyl ether	(CAS No) 60-29-7	10 - 30	Flam. Liq. 1 Acute Tox. 4 (Oral) STOT SE 3
Carbon dioxide	(CAS No) 124-38-9	3 - 7	Compressed gas
n-Heptane	(CAS No) 142-82-5	1 - 5	Flam. Liq. 2 Skin Irrit. 2 STOT SE 3
Ethyl alcohol	(CAS No) 64-17-5	0.5 - 1.5	Flam. Liq. 2 Eye Irrit. 2A
Ethyl chloride	(CAS No) 75-00-3	0.1 - 1	Flam. Gas 1 Liquefied gas Carc. 2
Toluene	(CAS No) 108-88-3	< 0.1	Flam. Liq. 2 Acute Tox. 4 (Oral) Skin Irrit. 2 Repr. 2 STOT SE 3 STOT RE 2 Asp. Tox. 1

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures after inhalation	: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
First-aid measures after eye contact	: In case of contact, immediately flush eyes with plenty of water. Remove contact lenses, if worn. irritation persists, get medical attention.
First-aid measures after ingestion	: If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never giv anything by mouth to an unconscious person. Get immediate medical advice/attention.
4.2. Most important symptoms and effe	cts, both acute and delayed
Symptoms/injuries after inhalation	: May cause drowsiness, dizziness and central nervous system depression. May cause respirato tract irritation.
Symptoms/injuries after skin contact	: Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking o the skin.
Symptoms/injuries after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.
	Il attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Firefighting measure	es de la companya de
5.1. Extinguishing media	
Suitable extinguishing media	: Powder, water spray, foam, carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.
5.2. Special hazards arising from the	e substance or mixture
Fire hazard	: Extremely flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon.
Explosion hazard	: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.
5.3. Advice for firefighters	
Protection during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Vapors may be heavier than air and may travel along the ground to a distant ignition source and flash back. Use water spray to keep fire-exposed containers cool.



Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 6: Accidental release measures			
6.1.	Personal precautions, protective equipment and emergency procedures		
Genera	l measures	: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition.	
6.2.	Methods and material for contain	ment and cleaning up	
For con	tainment	: Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).	
Method	s for cleaning up	: Scoop up material and place in a disposal container. Provide ventilation.	
6.3.	Reference to other sections		
See see	See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.		

SECTION 7: Handling and stora	ge
7.1. Precautions for safe handling	
Precautions for safe handling	: Keep away from sources of ignition No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid contact with skin and eyes. Do not swallow. Avoid breathing gas/mist/vapors/spray. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area.
Hygiene measures	: Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.
7.2. Conditions for safe storage, in	cluding any incompatibilities
Storage conditions	 Keep locked up and out of reach of children. Do not expose to temperatures exceeding 50°C/ 122°F. Store away from direct sunlight or other heat sources. Store in a well-ventilated place.

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

	Heptane, branched, cyclic and linear (426260-76-6)			
USA ACGIH	ACGIH TWA	Not applicable.		
USA OSHA	OSHA PEL (TWA)	Not applicable.		
Ethyl ether (60-29-7)				
USA ACGIH	ACGIH TWA (ppm)	400 ppm		
USA ACGIH	ACGIH STEL (ppm)	500 ppm		
USA OSHA	OSHA PEL (TWA) (mg/m ³)	1200 mg/m ³		
USA OSHA	OSHA PEL (TWA) (ppm)	400 ppm		
Carbon dioxide (124-3	8-9)			
USA ACGIH	ACGIH TWA (ppm)	5000 ppm		
USA ACGIH	ACGIH STEL (ppm)	30000 ppm		
USA OSHA	OSHA PEL (TWA) (mg/m ³)	9000 mg/m³		
USA OSHA	OSHA PEL (TWA) (ppm)	5000 ppm		
n-Heptane (142-82-5)				
USA ACGIH	ACGIH TWA (ppm)	400 ppm		
USA ACGIH	ACGIH STEL (ppm)	500 ppm		
USA OSHA	OSHA PEL (TWA) (mg/m ³)	2000 mg/m ³		
USA OSHA	OSHA PEL (TWA) (ppm)	500 ppm		
Ethyl alcohol (64-17-5	Ethyl alcohol (64-17-5)			
USA ACGIH	ACGIH STEL (ppm)	1000 ppm		
USA OSHA	OSHA PEL (TWA) (mg/m ³)	1900 mg/m³		
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm		

Ethyl chloride (75-00-3)			
USA ACGIH	ACGIH TWA (ppm)	100 ppm	
USA OSHA OSHA PEL (TWA) (mg/m ³) 2600 mg/m ³			



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Ethyl chloride (75-00-3)			
USA OSHA	OSHA PEL (TWA) (ppm)		1000 ppm
Toluene (108-88-3)			
USA ACGIH	ACGIH TWA (ppm)		20 ppm
USA OSHA	OSHA PEL (TWA) (ppm)		200 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)		300 ppm
8.2. Exposure controls			·
Appropriate engineering controls : Use ventila		se ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below ecommended exposure limits.	
Personal protective equipment	: Avoid all u	Avoid all unnecessary exposure.	
Hand protection	: Wear cher	Wear chemically resistant protective gloves.	
Eye protection : Safety glasses or		asses or goggles are recommended when using product.	
Skin and body protection : Wea		Wear suitable protective clothing.	
Respiratory protection : A NIOSH approved respirator is recommended in poorly ventilated areas or when perm exposure limits may be exceeded. Respirator selection must be based on known or an exposure levels, the hazards of the product and the safe working limits of the selected		espirator selection must be based on known or anticipated	
Environmental exposure control	: Maintain le	Maintain levels below Community environmental protection thresholds.	
Other information			erial is handled, processed or stored. Wash hands carefully ording to established industrial hygiene and safety practices.

SECTION 9: Physical and chemical properties		
9.1. Information on basic physical and	chemical properties	
Physical state	: Gas/Pressurized Liquid.	
Appearance	: Clear.	
Colour	: Colourless.	
Odour	: Solvent.	
Odour threshold	: No data available.	
рН	: No data available.	
Relative evaporation rate (butylacetate=1)	: No data available.	
Melting point	: No data available.	
Freezing point	: No data available.	
Boiling point	: No data available.	
Flash point	: No data available.	
Self ignition temperature	: No data available.	
Decomposition temperature	: No data available.	
Flammability (solid, gas)	: Flammable.	
Vapour pressure	: No data available.	
Relative vapour density at 20 °C	: No data available.	
Relative density	: No data available.	
Solubility	: No data available.	
Log Pow	: No data available.	
Log Kow	: No data available.	
Viscosity, kinematic	: No data available.	
Viscosity, dynamic	: No data available.	
Explosive properties	: No data available.	
Oxidising properties	: No data available.	
Explosive limits	: No data available.	
9.2. Other information		

No additional information available

SECTI	ON 10: Stability and reactivity		
10.1.	Reactivity		

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under normal storage conditions. Extremely flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn.



Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

ccording to the Hazard Communication Standard (CFR29	9 1910.1200) HazCom 2012.	
10.3. Possibility of hazardous reactions		
No dangerous reaction known under conditions of	f normal use.	
10.4. Conditions to avoid		
Heat. Incompatible materials. Sources of ignition.	Air contact. Direct sunlight. Moisture.	
10.5. Incompatible materials		
Acids. Chlorine. Oxidizers. Reducing agents 10.6. Hazardous decomposition products		
May include, and are not limited to: oxides of carb	non	
SECTION 11: Toxicological information	on	
11.1. Information on toxicological effects		
Acute toxicity	: Not classified	
0797		
LD50 oral rat	> 2000 mg/kg	
LD50 dermal rabbit	> 2000 mg/kg	
LC50 inhalation rat (mg/l)	> 5 mg/l/4h	
Ethyl ether (60-29-7)		
LD50 oral rat	1215 mg/kg	
LD50 dermal rabbit	>20 mL/kg	
n-Heptane (142-82-5)		
LD50 dermal rabbit	3000 mg/kg	
LC50 inhalation rat (mg/l)	103 g/m³/4h	
Ethyl alcohol (64-17-5)		
LD50 oral rat	7060 mg/kg	
LC50 inhalation rat (mg/l)	124.7 mg/l/4h	
Ethyl chloride (75-00-3)		
LC50 inhalation rat (mg/l)	152 g/m³/2h	
	102 Gill / 211	
Toluene (108-88-3)	5000 //	
LD50 oral rat	> 5000 mg/kg	
LD50 dermal rat LD50 dermal rabbit	12124 mg/kg 8390 mg/kg	
LC50 inhalation rat (mg/l)	28.1 mg/l/4h	
Skin corrosion/irritation	: Causes skin irritation.	
Serious eye damage/irritation	: Based on available data, the classification criteria are not met.	
Respiratory or skin sensitisation	: Based on available data, the classification criteria are not met.	
Germ cell mutagenicity Carcinogenicity	 Based on available data, the classification criteria are not met. Suspected of causing cancer. 	
Ethyl alcohol (64-17-5)	1	
IARC group	1 (in alcoholic beverages)	
Ethyl chloride (75-00-3)		
IARC group	3	
National Toxicity Program (NTP) Status	1	
Toluene (108-88-3)		
IARC group	3	
Reproductive toxicity	: Based on available data, the classification criteria are not met.	
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.	
Specific target organ toxicity (repeated exposure)	: Based on available data, the classification criteria are not met.	
Aspiration hazard	: May be fatal if swallowed and enters airways.	
Symptoms/injuries after inhalation	: May cause drowsiness, dizziness and central nervous system depression. May cause respirator	
Symptoms/injuries after skin contact	 tract irritation. Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking o the skin. 	
Symptoms/injuries after eye contact	 May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling. 	
Symptoms/injuries after ingestion	 May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting. 	
05/28/2014	EN (English) 5/7	



Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

according to the Hazard Communication Standard (CFR29	
SECTION 12: Ecological information	
12.1. Toxicity	
	: May cause long-term adverse effects in the aquatic environment.
12.2. Persistence and degradability	
0797	
Persistence and degradability	Not established.
12.3. Bioaccumulative potential	
0797	
Bioaccumulative potential	Not established.
12.4. Mobility in soil	
No additional information available	
12.5. Other adverse effects	
No additional information available	
SECTION 13: Disposal considerations	
13.1. Waste treatment methods	
Waste disposal recommendations	: This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.
Additional information	: Flammable vapours may accumulate in the container. Do not incinerate closed containers.
SECTION 14: Transport information	
In accordance with DOT	
14.1. UN number	
UN-No.	: UN1950
14.2. UN proper shipping name	
	: Aerosols flammable
Department of Transportation Hazard Classes Hazard labels	: 2.1
14.3. Additional information	
Other information	: No supplementary information available.
Special transport precautions	: Do not handle until all safety precautions have been read and understood.
SECTION 15: Regulatory information	
15.1. US Federal regulations	
Heptane, branched, cyclic and linear (426260-	.76-6)
Listed on the United States TSCA (Toxic Substa	nces Control Act) inventory
Ethyl ether (60-29-7)	
Listed on the United States TSCA (Toxic Substan	nces Control Act) inventory
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
Carbon dioxide (124-38-9)	
Listed on the United States TSCA (Toxic Substa	nces Control Act) inventory
n-Heptane (142-82-5)	
Listed on the United States TSCA (Toxic Substa	nces Control Act) inventory
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
Ethyl alcohol (64-17-5)	
Listed on the United States TSCA (Toxic Substa	nces Control Act) inventory
Ethyl chloride (75-00-3)	
Listed on the United States TSCA (Toxic Substat Listed on SARA Section 313 (Specific toxic chem	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
SARA Section 313 - Emission Reporting	1.0 %


Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Toluene (108-88-3)					
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on SARA Section 313 (Specific toxic chemical listings)					
SARA Section 313 - Emission Reporting	1.0 %				
15.2. US State regulations					
0797					
State or local regulations	This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.				

SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

IARC	International Agency for Research on Cancer.
	 Carcinogenic to humans; Probably carcinogenic to humans; Possibly carcinogenic to humans; Not classifiable; Probably not carcinogenic to humans.
NTP	National Toxicology Program.
	 Evidence of Carcinogenicity; Known Human Carcinogens; Reasonably anticipated to be Human Carcinogen; Substances delisted from report on Carcinogens; Twelfth Report - Items under consideration.

SECTION 16: Other information		
Indication of changes	:	None.
Date of issue	:	05/28/2014
Other information	:	None.
NFPA health hazard	:	2
NFPA fire hazard	:	4
NFPA reactivity	:	0



This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

