

Pro Form Products Ltd. 604 McGeachie Drive Milton, Ontario, L9T 3Y5 Canada 905-878-4990

PRODUCT: AVUS 5984 GENERAL PURPOSE ADHESIVE CLEANER

SECTION 01: Chemical product and company identification

AVUS 5984 GENERAL PURPOSE ADHESIVE CLEANER Product name..... Aftermarket Auto Parts Alliance, Inc. Manufactured for..... 2706 Treble Creek, Suite 100 San Antonio, TX 78258 IN CANADA CALL CANUTEC 1-888-226-8832 (CAN-UTEC) - IN THE UNITED STATES 24 hour emergency number:..... CALL CHEMTREC 1-800-424-9300. Material use..... Cleaning solution. This product should not be used for any other purpose other than the ones described in this section. For industrial use only - keep out of reach of children. Chemical family..... Mixture. June 15, 2016. Preparation date..... Hazard rate

SECTION 02: Hazards identification



Signal Word..... DANGER. Hazard Classification..... Flammable Liquid 2. Aspiration Toxicity 1. Skin Irritant 2. STOT SE 3. H225 Highly flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. Hazard Description..... Precautionary Statements..... P241 Use explosion proof equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing mists, vapours and sprays. P264 Wash hands thoroughly after handling. P271 Use only outdoors or in a well ventilated area. P280 Wear protective gloves and eye protection.
P321 - For specific treatment see section 4 on this SDS. P301 + P310 If swallowed
IMMEDIATELY CALL A POISON CONTROL CENTRE and follow instructions provided by Response the centre. P302 + P352 - If on skin: wash with plenty of water. . P303 + P361 + P353 If on skin or in hair: take off all contaminated clothing immediately. Rinse thoroughly with water and use safety shower . P304 + P340 - If inhaled remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTER/doctor if you feel unwell. P331 Do NOT induce vomiting. P332 + P313 - If skin irritation occurs get medical attention or advice. P362 + P364 - Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire - use dry chemical powder, CO2 or foam to extinguish. P233 Keep container tightly closed. P403 + P235 Store in well ventilated area. Keep cool. Storage..... P405 Store locked up. Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.

SECTION 03: COMPOSITION/INFORMATION ON INGREDIENTS					
HAZARDOUS INGREDIENTS	CAS#	WT. %			
Xylene Light Aliphatic Solvent Naphtha	1330-20-7 64742-89-8	40-70 15-40			

SECTION 04: First aid measures

Remove all contaminated clothing and immediately wash the exposed areas with copious amounts of water for a minimum of 30 minutes or up to 60 minutes for critical body areas. If irritation persists, seek medical attention.



PRODUCT: AVUS 5984 GENERAL PURPOSE ADHESIVE CLEANER

SECTION 04: First aid measures

person.

incident involving this product ensure that medical authorities are provided a copy of this

safety data sheet.

SECTION 05: Fire fighting measures

Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. Keep run-off water from entering sewers and other waterways. Dike for water control.

SECTION 06: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Methods and materials for containment and cleaning up

Ventilate area, eliminate all sources of ignition, sound alarm, avoid all skin and eye contact and avoid breathing vapours.

Dike area to contain the spill, prevent runoff from going into drains, absorb residual material with an inert absorbent, shovel or pump to a properly labelled container and dispose of as a hazardous waste.

SECTION 07: Handling and storage

apparatus. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Avoid breathing vapours or mist. Ground handling equipment. Handle and open container with care. Employees should wash hands and face before eating or drinking. Keep away from

heat, sparks, and open flame.

close to fertilizers, seeds and foodstuffs.

SECTION 08: Exposure controls / personal protection

INGREDIENTS	TWA ACGI	H TLV STEL	OSHA PEL	NPEL STEL	NIOSH REL
Xylene	50 ppm	150 ppm	100 ppm TWA	Not established	Not established
Light Aliphatic Solvent Naphtha	Not established	Not established	Not established	Not established	Not established
Eye/type Respiratory/type		Liquid chemical goggles Local exhaust ventilatio when contaminant level	n is recommended. W	ear an appropriate, pro ended exposure limits.	perly fitted respirator
Gloves/ typeClothing/type		Chemical resistant glov Wear adequate protecti	es.		
Footwear/typeOther/typeVentilation requirements		Safety boots per local re Emergency showers an Local exhaust at points	egulations. Id eye wash stations s	hould be available.	

SECTION 09: Physical and chemical properties

Physical state	Liquid.
Colour	
Odour	Hydrocarbon odour.
Odour threshold (ppm)	1 - 20 ppm.
Vapour pressure (mm Hg)	< 2.5 kpa @ 20°C.
Vapour density (air=1)	< 3.9.
pH	Not applicable.



PRODUCT: AVUS 5984 GENERAL PURPOSE ADHESIVE CLEANER

SECTION 09: Physical and chemical properties

Relative Density (Specific Gravity)..... 6.93 lb/usg - 0.83 g/mL.

Melting / Freezing point (deg C)..... No data.

Solubility..... Not soluble in water.

Initial boiling point / boiling range (deg C)..... 118°C.

Evaporation rate..... Not available. Flammability (solids and gases)..... Flammable liquid.

Flash point (deg C), method..... 14°C Closed Cup.

Auto ignition temperature (deg C)..... 320°C.

Coefficient of water\oil distribution...... Not available.

% Volatile by volume..... 100.

VOC...... 819.64 g/L - 6.84 lb/gal.

Viscosity...... Not available.

SECTION 10: Stability and reactivity

This is a stable material.

Chemical stability..... Stable at normal temperatures and pressures.

Hazardous polymerization will not occur. Possibility of hazardous reactions.....

Conditions to avoid..... Keep away from heat. Strong oxidizing agents. Incompatible materails.....

Hazardous decomposition products..... By fire:. Dense black smoke. Oxides of carbon (CO,CO2).

SECTION 11: Toxicological information

INGREDIENTS	LC50	LD50

6350 ppm 4 hours rat Xvlene >3523 mg/kg rat oral

3400 ppm 4hr rat >2000 mg/kg oral rat >2000 mg/kg Light Aliphatic Solvent Naphtha

dermal rat

Eye contact. Skin contact. Inhalation. Route of entry

May cause moderate to severe eye irritation. Can cause moderate skin irritation, defatting Effects of acute exposure..... and dermatitis. Excessive inhalation of vapours can cause respiratory irritation, dizziness,

headache, vomiting and unconsciousness. Ingestion is not a likely route of exposure. If ingested, however, this product may be absorbed and result in gastrointestinal irritation,

nausea, vomiting, and diarrhea.

Effects of chronic exposure..... Breathing high concentrations of vapour may cause anesthetic effects and serious health

effects. Prolonged or repeated skin contact may cause drying or cracking of skin. Intentional misuse by deliberately concentrating and inhaling this product may be harmful

or fatal

None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen. Carcinogenicity of material.....

Reproductive effects....... High level exposure to Xylene in some animal studies have been reported to cause health effects on the developing embryo/fetus. The relevance of this to humans is not known.

SECTION 12: Ecological information

Environmental..... Do not allow to enter waters, waste water or soil.

Biodegradability..... Not available.

SECTION 13: Disposal considerations

Waste disposal..... This material and its container must be disposed of as hazardous waste. Avoid release to

the environment. Dispose of waste in accordance with all applicable Federal,

Provincial/State and local regulations.

SECTION 14: Transport information

TDG Classification..... UN1993 - FLAMMABLE LIQUID, N.O.S. (Light Aliphatic Solvent Naphtha) - Class 3 -

Packing Group II - This product meets the Limited Quantity exemption when packaged in

containers less than 1 Litre. UN1993 - FLAMMABLE LIQUID, N.O.S. (Light Aliphatic Solvent Naphtha) - Class 3 -

DOT Classification (Road)..... Packing Group II.

UN1993 - FLAMMABLE LIQUID, N.O.S. (Light Aliphatic Solvent Naphtha) - Class 3 -IATA Classification (Air).....

Packing Group II.

IMDG Classification (Marine)..... UN1993 - Flammable Liquid, NOS (Light Aliphatic Solvent Naphtha) - Class 3 - Packing

Group II - EmS: F-E,S-E.



PRODUCT: AVUS 5984 GENERAL PURPOSE ADHESIVE CLEANER

SECTION 14: Transport information

2, 2014) - we certify that classification of this product is correct. .

SECTION 15: Regulatory information

CEPA status...... On Domestic Substances List (DSL).

OSHA...... This product is considered hazardous under the OSHA Hazard Communication Standard.

SARA Title III

Section 302 - extremely hazardous None.

substances

Section 311/312 - hazard categories...... Immediate health, delayed health, fire hazard.

40CFR63

TSCA inventory status...... All components are listed.

California Proposition 65...... This product does not contain any chemical(s) listed on California's Proposition 65.

SECTION 16: Other information

Prepared by: REGULATORY AFFAIRS.

Telephone number:...... (800) 387-7981.

Disclaimer: DisCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed

experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not

relate to its use in combination with any other material or in any other process.