<b>ASHLAND</b>	Page: 1
SAFETY DATA SHEET	Revision Date: 05/23/2015
	Print Date: 6/11/2015
	SDS Number: 000000224341
PARTS Master® HIGH MILEAGE SAE 5W-30 MOTOR OIL	Version: 1.0
851585	

29 CFR 1910.1200 (OSHA HazCom 2012)

## **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

**Product identifier** 

Trade name : PARTS Master® HIGH MILEAGE SAE 5W-30

MOTOR OIL

## Recommended use of the chemical and restrictions on use

Details of the supplier of the safety data	Emergency telephone number
sheet	1-800-ASHLAND (1-800-274-5263)
Ashland	
P.O. Box 2219	Regulatory Information Number
Columbus, OH 43216	1-800-325-3751
United States of America	
	Product Information
	614-790-3333
EHS Customer Requests@ashland.com	
•	

### **SECTION 2. HAZARDS IDENTIFICATION**

## **GHS Classification**

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

## **GHS Label element**

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

### Other hazards

None known.

## **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

Chemical nature : Defatter

### **Hazardous components**

Chemical Name	CAS-No.	Classification	Concentration (%)
Benzenesulfonic acid, C10-60-alkyl derivs., sodium salts	90194-32-4	Eye Irrit. 2A; H319	6.26

<b>ASHLAND</b>	Page: 2
SAFETY DATA SHEET	Revision Date: 05/23/2015
	Print Date: 6/11/2015
	SDS Number: 000000224341
PARTS Master® HIGH MILEAGE SAE 5W-30 MOTOR OIL	Version: 1.0
851585	

HYDROTREATED LIGHT	64742-55-8	Asp. Tox. 1; H304	1.10	
PARAFFINIC DISTILLATE				

#### **SECTION 4. FIRST AID MEASURES**

General advice : No hazards which require special first aid measures.

If inhaled : If breathed in, move person into fresh air.

If unconscious place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

If swallowed : Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

: Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through

the skin may include:

stomach or intestinal upset (nausea, vomiting, diarrhea)

irritation (nose, throat, airways)

Notes to physician : No hazards which require special first aid measures.

## **SECTION 5. FIREFIGHTING MEASURES**

ASHLAND.	Page: 3
SAFETY DATA SHEET	Revision Date: 05/23/2015
	Print Date: 6/11/2015
	SDS Number: 000000224341
PARTS Master® HIGH MILEAGE SAE 5W-30 MOTOR OIL	Version: 1.0
851585	

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray Foam

Carbon dioxide (CO2)

Dry chemical

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: carbon dioxide and carbon monoxide

Hydrocarbons

Specific extinguishing

methods

Further information : Standard procedure for chemical fires.

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

Product is compatible with standard fire-fighting agents.

### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

### **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Conditions for safe storage : Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : No materials to be especially mentioned.

<b>ASHLAND</b>	Page: 4
SAFETY DATA SHEET	Revision Date: 05/23/2015
	Print Date: 6/11/2015
	SDS Number: 000000224341
PARTS Master® HIGH MILEAGE SAE 5W-30 MOTOR OIL	Version: 1.0
851585	

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	REL	5 mg/m3 Mist.	NIOSH/GUID E
		STEL	10 mg/m3 Mist.	NIOSH/GUID E
		PEL	5 mg/m3 Mist.	OSHA_TRA NS

**Engineering measures** : General room ventilation should be adequate for normal

conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known,

suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally

required.

Eye protection : Not required under normal conditions of use. Wear splash-

proof safety goggles if material could be misted or splashed

into eyes.

Skin and body protection : Wear resistant gloves (consult your safety equipment

supplier).

Wear as appropriate:

Safety shoes

Hygiene measures : General industrial hygiene practice.

### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Physical state : liquid

Odour : No data available

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

<b>ASHLAND</b>	Paç	ge: 5
SAFETY DATA SHEET	Revision Date: 05/23/2	2015
	Print Date: 6/11/2	2015
	SDS Number: 000000224	1341
PARTS Master® HIGH MILEAGE SAE 5W-30 MOTOR OIL	Version:	1.0
851585		

Boiling point/boiling range : No data available

Flash point :  $> 390 \, ^{\circ}\text{F} \, / > 199 \, ^{\circ}\text{C}$ 

Method: Cleveland open cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : 1.3333333 hPa (20 °C)

Calculated Vapor Pressure

Relative vapour density : No data available

Relative density : No data available

Density : 0.8719 g/cm3 (15.6 °C)

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 68.8 mm2/s (40 °C)

Oxidizing properties : No data available

## **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Product will not undergo hazardous polymerization.

Conditions to avoid : excessive heat

<b>ASHLAND</b>	Page: 6
SAFETY DATA SHEET	Revision Date: 05/23/2015
	Print Date: 6/11/2015
	SDS Number: 000000224341
PARTS Master® HIGH MILEAGE SAE 5W-30 MOTOR OIL	Version: 1.0
851585	

Incompatible materials : Oxidizing agents

Hazardous decomposition

products carbon dioxide and carbon monoxide

Hydrocarbons

### **SECTION 11. TOXICOLOGICAL INFORMATION**

Information on likely routes of : Inhalation

exposure Skin contact

Eye Contact Ingestion

### **Acute toxicity**

Not classified based on available information.

### Skin corrosion/irritation

Not classified based on available information.

# Product:

Result: Repeated exposure may cause skin dryness or cracking.

### Components:

Benzenesulfonic acid, C10-60-alkyl derivs., sodium salts:

Result: Not irritating to skin

## HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result: Mildly irritating to skin

## Serious eye damage/eye irritation

Not classified based on available information.

**Product:** 

Remarks: Unlikely to cause eye irritation or injury.

## **Components:**

Benzenesulfonic acid, C10-60-alkyl derivs., sodium salts:

Result: Irritating to eyes

# HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result: Mildly irritating to eyes

# Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

### Germ cell mutagenicity

Not classified based on available information.

## Carcinogenicity

Not classified based on available information.

# Reproductive toxicity

Not classified based on available information.

<b>ASHLAND</b>	Page: 7
SAFETY DATA SHEET	Revision Date: 05/23/2015
	Print Date: 6/11/2015
	SDS Number: 000000224341
PARTS Master® HIGH MILEAGE SAE 5W-30 MOTOR OIL	Version: 1.0
851585	

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

**Aspiration toxicity** 

Not classified based on available information.

**Components:** 

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

**Further information** 

**Product:** 

Remarks: No data available

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

#### **SECTION 12. ECOLOGICAL INFORMATION**

## **Ecotoxicity**

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

**Product:** 

Additional ecological

information

: No data available

<b>ASHLAND</b>	Page: 8
SAFETY DATA SHEET	Revision Date: 05/23/2015
	Print Date: 6/11/2015
	SDS Number: 000000224341
PARTS Master® HIGH MILEAGE SAE 5W-30 MOTOR OIL	Version: 1.0
851585	

## **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

General advice : Dispose of in accordance with all applicable local, state and

federal regulations.

Contaminated packaging : Empty remaining contents.

# **SECTION 14. TRANSPORT INFORMATION**

# International transport regulations

### **REGULATION**

ID NUMBER	PROPER SHIPPING NAME	*HAZARD	SUBSIDIARY	PACKING	MARINE
		CLASS	HAZARDS	GROUP	POLLUTANT /
					LTD. QTY.

### **U.S. DOT - ROAD**

Not dangerous goods

# U.S. DOT - RAIL

Not dangerous goods	

### **U.S. DOT - INLAND WATERWAYS**

Not dangerous goods	

## TRANSPORT CANADA - ROAD

Not dangerous goods	

## TRANSPORT CANADA - RAIL

Not dangerous goods	

# TRANSPORT CANADA - INLAND WATERWAYS

Not dangerous goods	

# **INTERNATIONAL MARITIME DANGEROUS GOODS**

Not dangerous goods	

## **INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO**

Not dangerous goods	

<b>ASHLAND</b>	Page: 9
SAFETY DATA SHEET	Revision Date: 05/23/2015
	Print Date: 6/11/2015
	SDS Number: 000000224341
PARTS Master® HIGH MILEAGE SAE 5W-30 MOTOR OIL	Version: 1.0
851585	

### INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

# MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND **WASTES**

Not dangerous goods

### \*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

#### **SECTION 15. REGULATORY INFORMATION**

SARA 311/312 Hazards : No SARA Hazards

**SARA 313** 

: This material does not contain any chemical components with Component(s)SARA 313 known CAS numbers that exceed the threshold (De Minimis)

reporting levels established by SARA Title III, Section 313.

Pennsylvania Right To Know

HEAVY PARAFFINIC DISTILLATE 64742-54-7 90.00 -100.00 % 90194-32-4 5.00 - 10.00 % Benzenesulfonic acid, C10-60-alkyl derivs.,

sodium salts

HYDROTREATED LIGHT PARAFFINIC 64742-55-8 1.00 - 5.00 %

DISTILLATE

**New Jersey Right To Know** 

HEAVY PARAFFINIC DISTILLATE 64742-54-7 90.00 -100.00 %

Benzenesulfonic acid, C10-60-alkyl derivs., 90194-32-4 5.00 - 10.00 %

sodium salts

POLYOLEFIN AMIDE ALKENEAMINE Not Assigned 1.00 - 5.00 %

LUBRICANT ADDITIVE Not Assigned 1.00 - 5.00 %

Gas oils, petroleum, vacuum, hydrocracked, 178603-65-1 1.00 - 5.00 %

hydroisomerized, hydrogenated, C20-40,

branched and cyclic

<b>ASHLAND</b>	Page: 10
SAFETY DATA SHEET	Revision Date: 05/23/2015
	Print Date: 6/11/2015
	SDS Number: 000000224341
PARTS Master® HIGH MILEAGE SAE 5W-30 MOTOR OIL	Version: 1.0
851585	

HYDROTREATED LIGHT PARAFFINIC DISTILLATE

64742-55-8

1.00 - 5.00 %

California Prop 65

Proposition 65 warnings are not required for this product

based on the results of a risk assessment.

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL.

AUSTR : On the inventory, or in compliance with the inventory

NZIOC : Not in compliance with the inventory

ENCS : Not in compliance with the inventory

KECL : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : q (quantity restricted)


#### **Inventories**

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

#### **SECTION 16. OTHER INFORMATION**

#### **Further information**

Revision Date: 05/23/2015



### NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

<b>ASHLAND</b>	Page: 11
SAFETY DATA SHEET	Revision Date: 05/23/2015
	Print Date: 6/11/2015
	SDS Number: 000000224341
PARTS Master® HIGH MILEAGE SAE 5W-30 MOTOR OIL	Version: 1.0
851585	

#### Full text of H-Statements referred to under sections 2 and 3.

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.

Sources of key data used to compile the Safety Data Sheet
Ashland internal data including own and sponsored test reports
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet:

ACGIH: American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV: Threshold Limit Value TWA: Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

<b>ASHLAND</b>	Page: 12
SAFETY DATA SHEET	Revision Date: 05/23/2015
	Print Date: 6/11/2015
	SDS Number: 000000224341
PARTS Master® HIGH MILEAGE SAE 5W-30 MOTOR OIL	Version: 1.0
851585	

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

DOT : Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act HMIRC : Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety and Health Administration

PMRA: Health Canada Pest Management Regulatory Agency

RTK: Right to Know

WHMIS: Workplace Hazardous Materials Information System