

## **Safety Data Sheet I. PRODUCT AND COMPANY IDENTIFICATION**

Product Name:	PERSTOP DOT3 BRK FL 55GL		
Product Code:	PS20BF55		
<b>Emergency Phone:</b>	CHEMTREC: +1 (800) 424-9300		
	International: +01 (703) 527-3887		
Poison Control	(800) 222-1222		
Center:			
Company:	Warren Distribution, Inc.		
	727 S. 13th Street		
	Omaha, NE 68102		
Information Phone:	+01 (800) 825-1235 +01 (402) 341-9397		
E-mail:	sds@wd-wpp.com		

### **II. HAZARDS IDENTIFICATION**

<b>Routes of Entry:</b>	Inhalation, Ingestion, Skin contact, Eye contact
Target Organs:	Eyes, Skin, Kidneys
<b>Chemical Interactions:</b>	None known.
<b>Conditions Aggravated</b>	Skin disease including eczema and sensitization, Eye disease, Kidney disease
by Exposure:	

Acute Health Effects:	
Inhalation Irritation:	No hazard in normal industrial use.
Skin Contact:	Can cause minor skin irritation, defatting, and dermatitis.
Skin Absorption:	No absorption hazard in normal industrial use.
Eye Contact:	Contact with the eyes may cause moderate to severe eye injury. Eye contact may result
Ingestion Irritation:	in tearing and reddening, but not likely to permanently injure eye tissue. Temporary vision impairment (cloudy or blurred vision) is possible. May be harmful or fatal if swallowed. Excessive exposure may cause central nervous system effects, cardiopulmonary effects (metabolic acidosis), kidney failure, or death.
Chronic Health Effects:	
Consingeration	Not a consistence according to NTD IADC or OSUA

<b>Carcinogenicity:</b>	Not a carcinogen according to NTP, IARC, or OSHA.
Reproductive	No data available to indicate product or any components present at greater than 0.1%
Toxicity:	may cause birth defects.
Mutagenicity:	No data available to indicate product or any components present at greater than 0.1% is
	mutagenic or genotoxic.

		HMIS R	atings:	NFPA Rating	<u>is:</u>		
		Health:	3	Health:	3		
		Fire:	1	Fire:	1		
		Reactivit	y: 0	Reactivity:	0		
		PPE:	В				
I	KEY:	0 - Least	1 - Slight	2 - Moderate	3 - H	igh -	4 – Extreme

### **III. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	%	CAS #	OSHA Exposure Limits
Ethanol, 2-(2-(2-butoxyethoxy)ethoxy)-	15 - 40	143-22-6	
Ethanol, 2-(2-(2-ethoxyethoxy)ethoxy)-	10 - 30	112-50-5	
Diethylene glycol	10 - 30	111-46-6	
Ethanol, 2-(2-(2-methoxyethoxy)ethoxy)-	7 - 13	112-35-6	
Tetraethylene glycol monobutyl ether	5 - 10	1559-34-8	
Components not listed are not physical or health	hozorda og dafinad i	20 CEP 1010	1200 (Hazard Communication

Components not listed are not physical or health hazards as defined in 29 CFR 1910.1200 (Hazard Communication Standard).

### **IV. FIRST-AID MEASURES**

Inhalation:	This material does not present a hazard if inhaled. Remove individual to fresh air after
	an airborne exposure if any symptoms develop, as a precautionary measure.
Eyes:	Immediately flush eyes with plenty of water for at least 20 minutes retracting eyelids
	often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get
	immediate medical attention and monitor the eye daily as advised by your physician.
Skin Contact:	Wash with soap and water. Get medical attention if irritation develops or persists.
Ingestion:	No hazard in normal industrial use. Do not induce vomiting. Seek medical attention if
	symptoms develop. Provide medical care provider with this SDS.
Notes to Doctor:	No additional first aid information available.

### **V. FIRE FIGHTING MEASURES**

Flammability	Combustible at elevated temperatures
Summary:	
Extinguishing Media:	Use alcohol resistant foam, carbon dioxide, or dry chemical when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the surface of the fire. Do not direct a stream of water into the hot burning liquid.
Fire and/or Explosion Hazards:	Material may be ignited only if preheated to temperatures above the high flash point, for example in a fire.
nazarus:	example in a me.
Fire Fighting Methods and Protection:	Do not enter fire area without proper protection including self- contained breathing
and Protection:	apparatus and full protective equipment. Use methods for the surrounding fire.
Hazardous	Carbon monoxide, Carbon dioxide, Nitrogen containing gases
<b>Combustion Products:</b>	

### VI. ACCIDENTAL RELEASE MEASURES

<b>Personal Precautions</b>	Exposure to the spilled material may be severely irritating or toxic. Follow personal
and Equipment:	protective equipment recommendations found in Section 8 of this SDS. Personal
	protective equipment needs must be evaluated based on the special circumstances
	created by the spill including; the material spilled, the quantity of the spill, the area in
	which the spill occurred, and the expertise of employees in the area responding to the
	spill. Never exceed any occupational exposure limits.
Methods for Clean-up:	Prevent the spread of any spill to minimize harm to human health and the environment if
_	safe to do so. Wear complete and proper personal protective equipment following the
	recommendation of Section 8 at a minimum. Dike with suitable absorbent material.
	Gather and store in a sealed container pending a waste disposal evaluation. Do not flush
	to sewer.

#### VII. HANDLING AND STORAGE

Handling Precautions:	Mildly irritating material. Avoid unnecessary exposure.		
Storage Conditions:	Store in a cool dry place. Isolate from incompatible materials.		

### VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls:	No engineering controls are likely to be required to maintain operator comfort under normal conditions of use.
Respiratory	No respiratory protection required under normal conditions of use.
Protection:	
<b>Respirator Type(s):</b>	None required where adequate ventilation is provided. If airborne concentrations are above the applicable exposure limits, use NIOSH/MSHA approved respiratory protection.
Eye Protection:	Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Do not wear contact lenses. Have an eye wash station available.
Skin Protection:	Where use can result in skin contact, practice good personal hygiene and wear

**Gloves:** 

impervious gloves. Wash hands and other exposed areas with mild soap and water
before eating, drinking, and when leaving work. Where contact is likely, wear chemical
resistant gloves, a chemical suit, rubber boots, and chemical safety goggles plus a face
shield.

Butyl rubber, Natural latex,, Polyvinyl chloride

Chemical Name	<b>Occupational Exposure Limits</b>	Value
None.	OSHA PEL	
None.	IDLH	
None.	OSHA PEL-Skin Notation	

### X. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid
Color:	Colorless to pale yellow
Odor:	Strong
pH:	8.6
Solubility in Water:	Complete; 100%
Octanol/Water	Not determined
<b>Partition Coefficient:</b>	
<b>Evaporation Rate:</b>	Not determined
Vapor Density:	6
Vapor Pressure:	Not determined
Boiling Point (°C):	260
Freezing Point (°C):	Not determined
Specific Gravity:	1.04
Density:	8.71
Flash Point (°C):	138
Flash Point Method:	ASTM D 93
Upper Flammability	Not established
Limit, % in air:	
Lower Flammability	Not established
Limit, % in air:	

### X. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions.
<b>Conditions to Avoid:</b>	Temperatures above the high flash point of this combustible material in combination
	with sparks, open flames, or other sources of ignition. Dried product residue (can act as
	an oxidizer). Impact or high temperatures can cause decomposition
Materials to Avoid:	Strong acids, Strong oxidizing agents
Hazardous Decomp.	Aldehydes
Products:	
Hazardous	Hazardous polymerization will not occur.
Polymerization:	

# XI. TOXICOLOGICAL INFORMATION

<u>Acute Toxicity:</u>	
Ingestion:	Although this product has a low order of acute oral toxicity, aspiration of minute amounts into the lungs during ingestion or vomiting may cause mild to severe
	pulmonary injury and possibly death.
Inhalation:	No hazard in normal industrial use.
Absorption:	No absorption hazard in normal industrial use.
Eyes:	This material is likely to be severely irritating to eyes based on animal data.
Skin:	This material is estimated to be slightly irritating (Primary Irritation Index is 0.5 - 3.0 [rabbits]).
Sensitization:	No data available to indicate product or components may be a skin sensitizer.

PERSTOP DOT3 BRK FL 55GL

Component Toxicology Data:		
Chemical Name	CAS #	LD50/LC50
Ethanol, 2-(2-(2-butoxyethoxy)ethoxy)-	143-22-6	Oral LD50 Rat 5300 mg/kg (Source: IUCLID); Dermal LD50 Rabbit 3480 mg/kg (Source: IUCLID)
Ethanol, 2-(2-(2-ethoxyethoxy)ethoxy)-	112-50-5	Oral LD50 Rat 7750 mg/kg; Dermal LD50 Rabbit 3540 mg/kg
Diethylene glycol	111-46-6	Dermal LD50 Rabbit 11890 mg/kg (Source: NLM_CIP); Oral LD50 Rat 12565 mg/kg (Source: IUCLID)
3,6,9,12-Tetraoxahexadecan-1-ol	1559-34-8	Oral LD50 Rat 5175 mg/kg (Source: IUCLID); Dermal LD50 Rat >4000 mg/kg (Source: IUCLID)

### XII. ECOLOGICAL INFORMATION

Mobility:		is expected to here. {EMSFORM	ave essentially no mobility in soil. It absor _12MOBA}	bs strongly to
Bioconcentration: Degradability:	Bioconcentration is not expected to occur. Biodegrades at a moderate rate.			
Toxicity to Aquatic In	vertebrates:	CAS #	Results	

Toxicity to Aquatic Invertebrates:	CAS #	Results
Triethylene glycol monobutyl ether	143-22-6	48 Hr EC50 Daphnia magna: >500 mg/L
Diethylene glycol	111-46-6	48 Hr EC50 Daphnia magna: 84000 mg/L
Triethylene glycol monomethyl ether	112-35-6	48 Hr EC50 Daphnia magna: >500 mg/L
3,6,9,12-Tetraoxahexadecan-1-ol	1559-34-8	48 Hr EC50 Daphnia magna: >1000 mg/L
Triethylene glycol monobutyl ether	143-22-6	72 Hr EC50 Desmodesmus subspicatus: >500 mg/L
Triethylene glycol monomethyl ether	112-35-6	72 Hr EC50 Desmodesmus subspicatus: >500 mg/L
3,6,9,12-Tetraoxahexadecan-1-ol	1559-34-8	96 Hr EC50 Pseudokirchneriella subcapitata: >1000
		mg/L
Toxicity to Fish:	CAS #	Results
Triethylene glycol monobutyl ether	143-22-6	96 Hr LC50 Leuciscus idus: 2200 - 4600 mg/L
		[static]; 96 Hr LC50 Pimephales promelas: 2400
		[static]; 96 Hr LC50 Pimephales promelas: 2400 mg/L [static]; 96 Hr LC50 Pimephales promelas:
Diethylene glycol	111-46-6	mg/L [static]; 96 Hr LC50 Pimephales promelas:
	111-46-6	mg/L [static]; 96 Hr LC50 Pimephales promelas: 2400 mg/L 96 Hr LC50 Pimephales promelas: 75200 mg/L [flow-through]
Diethylene glycol Triethylene glycol monomethyl ether	111-46-6 112-35-6	mg/L [static]; 96 Hr LC50 Pimephales promelas: 2400 mg/L 96 Hr LC50 Pimephales promelas: 75200 mg/L [flow-through] 96 Hr LC50 Pimephales promelas: >10000 mg/L
		mg/L [static]; 96 Hr LC50 Pimephales promelas: 2400 mg/L 96 Hr LC50 Pimephales promelas: 75200 mg/L [flow-through] 96 Hr LC50 Pimephales promelas: >10000 mg/L [static]; 96 Hr LC50 Brachydanio rerio: >5000 mg/L
		<ul> <li>mg/L [static]; 96 Hr LC50 Pimephales promelas:</li> <li>2400 mg/L</li> <li>96 Hr LC50 Pimephales promelas: 75200 mg/L</li> <li>[flow-through]</li> <li>96 Hr LC50 Pimephales promelas: &gt;10000 mg/L</li> <li>[static]; 96 Hr LC50 Brachydanio rerio: &gt;5000 mg/L</li> <li>[static]; 96 Hr LC50 Leuciscus idus: &gt;10000 mg/L</li> </ul>
Triethylene glycol monomethyl ether		mg/L [static]; 96 Hr LC50 Pimephales promelas: 2400 mg/L 96 Hr LC50 Pimephales promelas: 75200 mg/L [flow-through] 96 Hr LC50 Pimephales promelas: >10000 mg/L [static]; 96 Hr LC50 Brachydanio rerio: >5000 mg/L [static]; 96 Hr LC50 Leuciscus idus: >10000 mg/L [static]
		<ul> <li>mg/L [static]; 96 Hr LC50 Pimephales promelas:</li> <li>2400 mg/L</li> <li>96 Hr LC50 Pimephales promelas: 75200 mg/L</li> <li>[flow-through]</li> <li>96 Hr LC50 Pimephales promelas: &gt;10000 mg/L</li> <li>[static]; 96 Hr LC50 Brachydanio rerio: &gt;5000 mg/L</li> <li>[static]; 96 Hr LC50 Leuciscus idus: &gt;10000 mg/L</li> </ul>

### XIII. DISPOSAL CONSIDERATIONS

Disposal of Packaging:Recycle containers whenever possible.Disposal Methods:Dispose of according to Federal, State, Local, or Provincial regulations.

### XIV. TRANSPORTATION INFORMATION

**D.O.T.** Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO).

<b>TSCA Status:</b>	All components of this material are of	on the US TSCA Ir	iventory or are exempt.
State Restrictions:	Not applicable		
WHMIS:	D2B		
Chemical Name	Regulation	CAS #	% Range
None.	CERCLA RQ		
None.	SARA 313		
None.	SARA 302-EHS		
None.	TSCA 12b export		
	notification		
None.	CA Prop 65 – Cancer		
None.	CA Prop 65 - Dev. Toxicity		
None.	CA Prop 65 - Reprod –fem		
None.	CA Prop 65 - Reprod –male		
Diethylene glycol	Canadian WHMIS List	111-46-6	10 - 30
None.	Massachusetts RTK List		
None.	New Jersey RTK List		
Ethanol, 2,2'-oxybis-	Pennsylvania RTK List	111-46-6	10 - 30
Diethylene glycol	Minnesota Hazardous	111-46-6	10 - 30
	Substance List		

### XV. REGULATORY INFORMATION

### **Consumer Product Safety Improvement Act of 2008 General Conformity Certification:**

This product has been evaluated and certified to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product container.

### XVI. ADDITIONAL INFORMATION

<b>XVI. ADDITION</b>	NAL INFORMATION
Supersedes:	2/23/2015 10:06:47 AM
<b>Revision Date:</b>	3/19/2015 4:30:28 PM
<b>References:</b>	ACGIH: American Conference of Governmental Industrial Hygienists
	AIHA: American Industrial Hygiene Association
	CFR: Code of Federal Regulations
	DOT: United States Department of Transportation
	GHS: Globally Harmonized System of Classification and Labeling of Chemicals
	HMIS: Hazardous Materials Identification System
	IARC: International Agency for Research on Cancer
	IATA: International Air Transportation Association
	IDLH: Immediately Dangerous to Life or Health
	IMDG: International Maritime Dangerous Goods
	NFPA: National Fire Protection Association
	NIOSH: National Institute for Occupational Safety and Health
	NTP: National Toxicology Program
	OSHA: Occupational Safety and Health Administration
	PEL: Permissible Exposure Limit
	RTK: Right-to-Know
	SARA: Superfund Amendments and Reauthorization Act
	STEL: Short-term Exposure Limit
	TLV: Threshold limit value
	TSCA: Toxic Substances Control Act
	TWA: Time weighted average
	UN: United Nations
	WHMIS: Workplace Hazardous Materials Information System
Disclaimer:	This safety data sheet and the information it contains is offered to you in good faith as accurate.
	We have reviewed any information contained in the data sheet which we have received from
	outside sources and we believe the information to be correct, but cannot guarantee its accuracy
	or completeness. Health and safety precautions in this data sheet may not be adequate for all
	individuals and/or situations. It is the user's obligation to evaluate and use this product in a safe
	manner and to comply with all applicable laws and regulations. No statement made in this data
	sheet shall be construed as permission or recommendation for the use of any product in a
	manner that might infringe existing patents. No warranty is made, either expressed or implied.