

I. PRODUCT AND COMPANY IDENTIFICATION

Product Name: PARTMSTR DEX VI ATF 6/1Q

Product Code: PMI6D6P6

Emergency Phone: CHEMTREC: +1 (800) 424-9300

International: +01 (703) 527-3887

Poison Control (800) 222-1222

Center:

Company: Warren Distribution, Inc.

727 S. 13th Street Omaha, NE 68102

Information Phone: +01 (800) 825-1235 +01 (402) 341-9397

E-mail: sds@wd-wpp.com

II. HAZARDS IDENTIFICATION

Routes of Entry: Skin contact, Eye contact, Ingestion, Inhalation

Target Organs: No organs known to be damaged from exposure to this product.

Chemical Interactions: No chemical interaction known to affect toxicity. **Conditions Aggravated** No medical conditions affected by exposure.

by Exposure:

Acute Health Effects:

Inhalation Irritation: Breathing oil mist in concentrations that exceed the TLV and PEL may result in

respiratory discomfort and irritation.

Skin Contact: Can cause minor skin irritation, defatting, and dermatitis.

Skin Absorption: No absorption hazard in normal industrial use.

Eye Contact: Can cause moderate irritation, tearing and reddening, but not likely to permanently

injure eye tissue.

Ingestion Irritation: No hazard in normal industrial use.

Chronic Health Effects:

Carcinogenicity: Not expected to cause cancer. This product meets the IP-346 criteria of <3% PAH's and

is not considered a carcinogen by the International Agency for Research on Cancer.

ReproductiveNo data available to indicate product or any components present at greater than 0.1%

Toxicity: may cause birth defects.

Mutagenicity: No data available to indicate product or any components present at greater than 0.1% is

mutagenic or genotoxic.

HMIS Ratings:NFPA Ratings:Health:1Health:1Fire:1Fire:1Reactivity:0Reactivity:0

PPE: B

KEY: 0 - Least 1 - Slight 2 - Moderate 3 - High 4 - Extreme

III. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name%CAS #OSHA Exposure LimitsLubricating oils (petroleum), C20-50, hydrotreated neutral oil-
based90 - 9972623-87-15 mg/m3

Amines, polyethylenepoly-, reaction products with Succinic 1 - 5 84605-20-9

anhydride polyisobutenyl derivitives

Components not listed are not physical or health hazards as defined in 29 CFR 1910.1200 (Hazard Communication Standard).

IV. FIRST-AID MEASURES

Inhalation: Remove to fresh air. If breathing is difficult, have a trained individual administer

oxygen.

Eyes: Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the

head to prevent chemical from transferring to the uncontaminated eye. Get immediate

medical attention.

Skin Contact: Wash with soap and water. Get medical attention if irritation develops or persists. **Ingestion:** No hazard in normal industrial use. Do not induce vomiting. Seek medical attention if

symptoms develop. Provide medical care provider with this SDS.

Notes to Doctor: No additional first aid information available.

V. FIRE FIGHTING MEASURES

Flammability Combustible at elevated temperatures

Summary:

Extinguishing Media: Use alcohol resistant foam, carbon dioxide, or dry chemical when fighting fires. Water

or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the surface of the fire. Do not direct a stream of water into

the hot burning liquid.

Fire and/or Explosion

Hazards:

Material may be ignited only if preheated to temperatures above the high flash point, for

example in a fire.

Fire Fighting Methods

and Protection: Hazardous Do not enter fire area without proper protection including self- contained breathing apparatus and full protective equipment. Use methods for the surrounding fire.

Carbon dioxide, Carbon monoxide

Combustion Products:

VI. ACCIDENTAL RELEASE MEASURES

Personal Precautions and Equipment:

Methods for Clean-up:

No health affects expected from the clean up of this material if contact can be avoided. Follow personal protective equipment recommendations found in Section 8 of this SDS. Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the

recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Dispose of according to Federal, State, Local, or Provincial regulations. Used fluid should be disposed of at a recycling center. Do not flush to sewer.

VII. HANDLING AND STORAGE

Handling Precautions: Mildly irritating material. Avoid unnecessary exposure. **Storage Conditions:** Store in a cool dry place. Isolate from incompatible materials.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Use local exhaust ventilation or other engineering controls to minimize exposures and

maintain operator comfort.

Respiratory Respiratory protection may be required to avoid overexposure when handling this

Protection: product. General or local exhaust ventilation is the preferred means of protection. Use a

respirator if general room ventilation is not available or sufficient to eliminate

symptoms.

Respirator Type(s): None required where adequate ventilation is provided. If airborne concentrations are

above the applicable exposure limits, use NIOSH/MSHA approved respiratory

protection.

Eye Protection: Wear chemically resistant safety glasses with side shields when handling this product.

Do not wear contact lenses.

Skin Protection: Where use can result in skin contact, practice good personal hygiene and wear

impervious gloves. Wash hands and other exposed areas with mild soap and water

before eating, drinking, and when leaving work.

Gloves: Nitrile

Chemical NameOccupational Exposure LimitsValueLubricating oils (petroleum), C20-50,OSHA PEL5 mg/m3

hydrotreated neutral oil-based

Lubricating oils (petroleum), C20-50, ACGIH TLV-TWA 5 mg/m3

hydrotreated neutral oil-based

Lubricating oils (petroleum), C20-50, ACGIH STEL 10 mg/m3

hydrotreated neutral oil-based

None. IDLH

None. OSHA PEL-Skin Notation

X. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:LiquidColor:RedOdor:Mild

pH: Not determined

Viscosity (cSt at 28.56

40°C):

Solubility in Water: Insoluble
Octanol/Water Not determined

Partition Coefficient:

Evaporation Rate: Not determined **Vapor Density:** Not determined

Vapor Pressure: <0.20

Boiling Point (°C): Not determined Freezing Point (°C): Not determined

Specific Gravity: 0.85

Density: 7.07

Flash Point (°C): 193

Flash Point Method: COC

Upper Flammability Not established

Limit, % in air:

Lower Flammability Not established

Limit, % in air:

X. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to Avoid: Temperatures above the high flash point of this combustible material in combination

with sparks, open flames, or other sources of ignition.

Materials to Avoid: Strong oxidizing agents

Hazardous Decomp. Carbon dioxide, Carbon monoxide

Products:

Hazardous Hazardous polymerization will not occur.

Polymerization:

XI. TOXICOLOGICAL INFORMATION

Acute Toxicity:

Ingestion: No hazard in normal industrial use.
Inhalation: No hazard in normal industrial use.

Absorption: No absorption hazard in normal industrial use.

Eyes: The material is likely to be moderately irritating to eyes based on animal data.

Skin: This material is estimated to be slightly irritating (Primary Irritation Index is 0.5 - 3.0

[rabbits]).

Sensitization: No data available to indicate product or components may be a skin sensitizer.

Component Toxicology Data:

Chemical Name CAS # LD50/LC50

Lubricating oils, petroleum, C20-50, hydrotreated 72623-87-1 Inhalation LC50 Rat 2.18 mg/L 4 h (Source: neutral oil-based IUCLID); Oral LD50 Rat >5000 mg/kg

(Source: IUCLID); Dermal LD50 Rabbit

>2000 mg/kg (Source: IUCLID)

XII. ECOLOGICAL INFORMATION

Mobility: This material is expected to have essentially no mobility in soil. It absorbs strongly to

most soil types. {EMSFORM_12MOBA}

Bioconcentration: Bioconcentration is not expected to occur.

Degradability: Does not biodegrade readily.

Toxicity to Aquatic Invertebrates: CAS # Results

Lubricating oils, petroleum, C20-50, 72623-87-1 48 Hr EC50 Daphnia magna: >1000 mg/L

hydrotreated neutral oil-based

Toxicity to Fish: CAS # Results

Lubricating oils, petroleum, C20-50, 72623-87-1 96 Hr LC50 Oncorhynchus mykiss: >5000 mg/L

hydrotreated neutral oil-based

XIII. DISPOSAL CONSIDERATIONS

Disposal of Packaging: Recycle containers whenever possible.

Disposal Methods: Dispose of according to Federal, State, Local, or Provincial regulations. Recycle used

oil.

XIV. TRANSPORTATION INFORMATION

D.O.T. Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO).

XV. REGULATORY INFORMATION

TSCA Status: All components of this material are on the US TSCA Inventory or are exempt.

State Restrictions: Not applicable

WHMIS: Uncontrolled product according to WHMIS classification criteria.

Chemical Name	Regulation	CAS#	% Range
None.	CERCLA RQ		
Arsenic	SARA 313	7440-38-2	<10ppm
Ethyl acrylate	SARA 313	140-88-5	<10ppm
Phenol	SARA 313	108-95-2	<10ppm
Ethylene glycol	SARA 313	107-21-1	<10ppm
Ethylene oxide	SARA 313	75-21-8	<10ppm
None.	SARA 302-EHS		
None.	TSCA 12b export		
	notification		
Ethyl acrylate	CA Prop 65 – Cancer	140-88-5	<10ppm
Ethylene oxide	CA Prop 65 – Cancer	75-21-8	<10ppm
Ethylene oxide	CA Prop 65 - Dev. Toxicity	75-21-8	<10ppm
Ethylene oxide	CA Prop 65 - Reprod –fem	75-21-8	<10ppm
Ethylene oxide	CA Prop 65 - Reprod -male	75-21-8	<10ppm
None.	Canadian WHMIS List		
None.	Massachusetts RTK List		
None.	New Jersey RTK List		
None.	Pennsylvania RTK List		

Chemical Name Regulation CAS # % Range

None. Minnesota Hazardous

Substance List

Consumer Product Safety Improvement Act of 2008 General Conformity Certification:

This product has been evaluated and certified to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product container.

XVI. ADDITIONAL INFORMATION

Supersedes: 1/23/2015 10:54:55 AM **Revision Date:** 2/26/2015 12:22:51 PM

References: ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CFR: Code of Federal Regulations

DOT: United States Department of Transportation

GHS: Globally Harmonized System of Classification and Labeling of Chemicals

HMIS: Hazardous Materials Identification System IARC: International Agency for Research on Cancer IATA: International Air Transportation Association IDLH: Immediately Dangerous to Life or Health IMDG: International Maritime Dangerous Goods NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health

NTP: National Toxicology Program

OSHA: Occupational Safety and Health Administration

PEL: Permissible Exposure Limit

RTK: Right-to-Know

SARA: Superfund Amendments and Reauthorization Act

STEL: Short-term Exposure Limit

TLV: Threshold limit value

TSCA: Toxic Substances Control Act

TWA: Time weighted average

UN: United Nations

WHMIS: Workplace Hazardous Materials Information System

Disclaimer: This safety data sheet and the information it contains is offered to you in good faith as accurate.

We have reviewed any information contained in the data sheet which we have received from outside sources and we believe the information to be correct, but cannot guarantee its accuracy or completeness. Health and safety precautions in this data sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product in a safe manner and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as permission or recommendation for the use of any product in a manner that might infringe existing patents. No warranty is made, either expressed or implied.