

# I. PRODUCT AND COMPANY IDENTIFICATION

Product Name: PM 85W-140 GL-5 3/1GL

**Product Code:** PMI5143P

**Emergency Phone:** CHEMTREC: +1 (800) 424-9300

International: +01 (703) 527-3887

**Poison Control** 

(800) 222-1222

Center: Company:

Warren Distribution, Inc.

727 S. 13th Street

Omaha, NE 68102

**Information Phone:** 

+01 (800) 825-1235 +01 (402) 341-9397

E-mail:

sds@wd-wpp.com

### II. HAZARDS IDENTIFICATION

Routes of Entry: Skin contact Target Organs: Skin

Target Organs: Ski

**Chemical Interactions:** No chemical interaction known to affect toxicity.

**Conditions Aggravated** 

by Exposure:

Personnel with pre-existing skin disorders should avoid contact with this product.

**Acute Health Effects:** 

**Inhalation Irritation:** Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and

headache.

**Skin Contact:** Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause

permanent damage. May cause skin irritation.

**Skin Absorption:** Minimal hazard in normal industrial use. May cause gastrointestinal discomfort.

**Eye Contact:** Can cause moderate irritation, tearing and reddening, but not likely to permanently

injure eye tissue.

**Ingestion Irritation:** No hazard in normal industrial use. Aspiration of material into the lungs can cause

chemical pneumonitis which can be fatal.

**Chronic Health Effects:** 

Carcinogenicity: Not expected to cause cancer. This product meets the IP-346 criteria of <3% PAH's and

is not considered a carcinogen by the International Agency for Research on Cancer.

**Reproductive**No data available to indicate product or any components present at greater than 0.1% may cause birth defects.

Mutagenicity: No data available to indicate product or any components present at greater than 0.1% is

mutagenic or genotoxic.

HMIS Ratings:NFPA Ratings:Health:2Health:2Fire:1Fire:1Reactivity:0Reactivity:0

PPE: B

KEY: 0 - Least 1 - Slight 2 - Moderate 3 - High 4 - Extreme

## III. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	<b>%</b>	CAS#	OSHA Exposure Limits
Residual oils (petroleum), solvent dewaxed	90 - 99	64742-62-7	
Petroleum distillates, hydrotreated heavy paraffinic	7 - 13	64742-54-7	5 mg/m3
Petroleum distillates, hydrotreated middle	0.1 - 1	64742-46-7	5 mg/m3

Components not listed are not physical or health hazards as defined in 29 CFR 1910.1200 (Hazard Communication Standard).

### IV. FIRST-AID MEASURES

Inhalation: Remove to fresh air. If breathing is difficult, have a trained individual administer

oxygen. If not breathing, give artificial respiration and have a trained individual

administer oxygen. Get medical attention immediately.

Eyes: Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the

head to prevent chemical from transferring to the uncontaminated eye. Get immediate

medical attention.

**Skin Contact:** Wash with soap and water. Remove contaminated clothing and launder. Get medical

attention if irritation develops or persists. Seek medical advice if symptoms persist.

No hazard in normal industrial use. Do not induce vomiting. Seek medical attention if **Ingestion:** 

> symptoms develop. Provide medical care provider with this SDS. Induce vomiting as a last measure. Induced vomiting may lead to aspiration of the material into the lungs

potentially causing chemical pneumonitis that may be fatal.

**Notes to Doctor:** Aspiration during swallowing or vomiting may severely damage the lungs. If evacuation

of stomach contents is necessary, use method least likely to cause aspiration.

## V. FIRE FIGHTING MEASURES

**Flammability** Combustible at elevated temperatures

**Summary:** 

**Extinguishing Media:** Use alcohol resistant foam, carbon dioxide, or dry chemical when fighting fires. Water

> or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the surface of the fire. Do not direct a stream of water into

> Material may be ignited only if preheated to temperatures above the high flash point, for

Do not enter fire area without proper protection including self- contained breathing

the hot burning liquid.

example in a fire.

Fire and/or Explosion

Hazards:

Fire Fighting Methods

and Protection:

apparatus and full protective equipment. Use methods for the surrounding fire. **Hazardous** Carbon monoxide, Smoke

**Combustion Products:** 

# VI. ACCIDENTAL RELEASE MEASURES

**Personal Precautions** and Equipment:

Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also

consider the expertise of employees in the area responding to the spill.

**Methods for Clean-up:** 

Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Dispose of according to Federal, State, Local, or Provincial regulations. Used fluid should be disposed of at a recycling center. Remove from water surface by skimming or with suitable absorbents. Do not use dispersants. Avoid runoff into storm

sewers and ditches that lead to waterways. Do not flush to sewer.

### VII. HANDLING AND STORAGE

**Handling Precautions:** Harmful or irritating material. Avoid contacting and avoid breathing the material. Use

only in a well ventilated area. Empty containers may retain product residues/ vapors.

Page 2 of 6

Use proper bonding and grounding during bulk product transfer.

**Storage Conditions:** Store in a cool dry place. Isolate from incompatible materials.

## VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Engineering Controls:** Use local exhaust ventilation or other engineering controls to minimize exposures and

maintain operator comfort.

Respiratory Respiratory protection may be required to avoid overexposure when handling this **Protection:** product. General or local exhaust ventilation is the preferred means of protection. Use a

PM 85W-140 GL-5 3/1GL

respirator if general room ventilation is not available or sufficient to eliminate

symptoms.

**Respirator Type(s):** None required where adequate ventilation is provided. If airborne concentrations are

above the applicable exposure limits, use NIOSH/MSHA approved respiratory

protection.

**Eye Protection:** Wear chemically resistant safety glasses with side shields when handling this product.

Do not wear contact lenses.

**Skin Protection:** Wear protective gloves. Inspect gloves for chemical break-through and replace at

regular intervals. Clean protective equipment regularly. Wash hands and other exposed

areas with mild soap and water before eating, drinking, and when leaving work.

Gloves: Neoprene, Nitrile

**Control Parameters:** 

Chemical Name ACGIH TLV ACGIH IDLH NIOSH
-TWA STEL STEL

Residual oils (petroleum), solvent dewaxed

Petroleum distillates, hydrotreated heavy paraffinic 5 mg/m3 10 mg/m3 Petroleum distillates, hydrotreated middle 5 mg/m3 10 mg/m3

# IX. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid Color: Amber Odor: Mild

**pH:** Not determined

Viscosity (cSt at

347.7

40°C):

**Solubility in Water:** Negligible; 0-1% **Octanol/Water** Not determined

**Partition Coefficient:** 

**Evaporation Rate:** Not determined **Vapor Density:** Not determined

**Vapor Pressure:** <0.20

**Boiling Point (°C):** Not determined

Freezing Point (°C): -20 Specific Gravity: 0.89 Density: 7.46 Flash Point (°C): 218 Flash Point Method: COC

**Upper Flammability** Not established

Limit, % in air:

Lower Flammability Not established

Limit, % in air:

# X. STABILITY AND REACTIVITY

Stability: Stable under normal conditions. Hazardous polymerization will not occur

**Conditions to Avoid:** Temperatures above the high flash point of this combustible material in combination

with sparks, open flames, or other sources of ignition. Moisture (will lead to product

performance degradation).

Materials to Avoid: Strong oxidizing agents
Hazardous Decomp. Carbon monoxide, Smoke

**Products:** 

**Hazardous** Hazardous polymerization will not occur.

**Polymerization:** 

### XI. TOXICOLOGICAL INFORMATION

**Acute Toxicity:** 

**Ingestion:** Although this product has a low order of acute oral toxicity, aspiration of minute

amounts into the lungs during ingestion or vomiting may cause mild to severe

pulmonary injury and possibly death.

**Inhalation:** Harmful! Can cause systemic damage (see "Target Organs").

Absorption: Minimal hazard in normal industrial use. May cause gastrointestinal discomfort.

Eyes: The material is likely to be moderately irritating to eyes based on animal data.

Skin: This material is likely to be moderately irritating to skin based on animal data.

Sensitization: No data available to indicate product or components may be a skin sensitizer.

**Component Toxicology Data:** 

Chemical Name	CAS#	LD50/LC50
Residual oils (petroleum), solvent dewaxed	64742-62-7	Inhalation LC50 Rat 2.18 mg/L 4 h (Source:
		IUCLID); Oral LD50 Rat >5000 mg/kg
		(Source: IUCLID); Dermal LD50 Rabbit
		>2000 mg/kg (Source: IUCLID)
Distillates (petroleum), hydrotreated heavy	64742-54-7	Inhalation LC50 Rat 2.18 mg/L 4 h; Oral
paraffinic		LD50 Rat >2000 mg/kg; Dermal LD50 Rabbit
		>2000 mg/kg
Polysulfides, di-tert-butyl	68937-96-2	Oral LD50 Rat 6500 mg/kg (Source: IUCLID)
Petroleum distillates, hydrotreated middle	64742-46-7	Inhalation LC50 Rat 4.6 mg/L 4 h (Source:
		IUCLID); Oral LD50 Rat 7400 mg/kg (Source:
		IUCLID); Dermal LD50 Rabbit >2000 mg/kg
		(Source: IUCLID)

#### XII. ECOLOGICAL INFORMATION

Overview: Slight ecological hazard. In high concentrations, this product may be dangerous to

plants and/or wildlife.

**Mobility:** This material is expected to have essentially no mobility in soil. It absorbs strongly to

Results

most soil types.

**Persistence:** Biodegradation, adsorption to sediment, and bioconcentration to aquatic organisms

should not be significant.

CAS#

**Bioconcentration:** Bioconcentration may occur.

**Degradability:** Biodegrades slowly.

**Toxicity to Aquatic Invertebrates:** 

Residual oils (petroleum), solvent dewaxed	64742-62-7	48 Hr EC50 Daphnia magna: >1000 mg/L
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	48 Hr EC50 Daphnia magna: >1000 mg/L
Toxicity to Fish:	CAS#	Results
Residual oils (petroleum), solvent dewaxed	64742-62-7	96 Hr LC50 Oncorhynchus mykiss: >5000 mg/L
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	96 Hr LC50 Oncorhynchus mykiss: >5000 mg/L
Polysulfides, di-tert-butyl	68937-96-2	96 Hr LC50 Pimephales promelas: 250 - 500 mg/L [static]; 96 Hr LC50 Pimephales promelas: >1000 mg/L [semi-static]
Petroleum distillates, hydrotreated middle	64742-46-7	96 Hr LC50 Pimephales promelas: 35 mg/L [flow-through]; 96 Hr LC50 Pimephales promelas: >10000 mg/L [static]

### XIII. DISPOSAL CONSIDERATIONS

**Disposal of Packaging:** Recycle containers whenever possible.

Containers of this material may be hazardous when emptied.

**Disposal Methods**: Dispose of according to Federal, State, Local, or Provincial regulations. Recycle used

oil.

### XIV. TRANSPORTATION INFORMATION

**D.O.T.** Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO).

### XV. REGULATORY INFORMATION

**TSCA Status:** All components of this material are on the US TSCA Inventory or are exempt.

**State Restrictions:** Not applicable

WHMIS: Uncontrolled product according to WHMIS classification criteria

Chemical Name	Regulation	CAS#	% Range
None.	CERCLA RQ		
Vinyl acetate	SARA 313	108-05-4	0.001- 0.01
Ethyl acrylate	SARA 313	140-88-5	<10ppm
1,4-Dioxane	SARA 313	123-91-1	<10ppm
Ethylene oxide	SARA 313	75-21-8	<10ppm
Propylene oxide	SARA 313	75-56-9	<10ppm
None.	SARA 302-EHS		
None.	TSCA 12b export		
	notification		
Ethyl acrylate	CA Prop 65 – Cancer	140-88-5	<10ppm
1,4-Dioxane	CA Prop 65 – Cancer	123-91-1	<10ppm
Ethylene oxide	CA Prop 65 – Cancer	75-21-8	<10ppm
Propylene oxide	CA Prop 65 – Cancer	75-56-9	<10ppm
Ethylene oxide	CA Prop 65 - Dev. Toxicity	75-21-8	<10ppm
Ethylene oxide	CA Prop 65 - Reprod –fem	75-21-8	<10ppm
Ethylene oxide	CA Prop 65 - Reprod -male	75-21-8	<10ppm
Hydrotreated middle distillate	Canadian WHMIS List	64742-46-7	0.1 - 1
(petroleum)			
None.	Massachusetts RTK List		
None.	New Jersey RTK List		
None.	Pennsylvania RTK List		
None.	Minnesota Hazardous		
	Substance List		

#### Consumer Product Safety Improvement Act of 2008 General Conformity Certification:

This product has been evaluated and certified to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product container.

# XVI. ADDITIONAL INFORMATION

 Supersedes:
 8/22/2014 10:47:52 AM

 Revision Date:
 8/27/2014 5:03:36 PM

**Disclaimer:** This safety data sheet and the information it contains is offered to you in good faith as accurate.

We have reviewed any information contained in the data sheet which we have received from outside sources and we believe the information to be correct, but cannot guarantee its accuracy or completeness. Health and safety precautions in this data sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product in a safe manner and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as permission or recommendation for the use of any product in a manner that might infringe existing patents. No warranty is made, either expressed or implied.