

<b>ASHLAND®</b>		Page: 1
<b>SAFETY DATA SHEET</b>		Revision Date: 06/02/2015
		Print Date: 6/11/2015
		SDS Number: R0091437
PARTS Master® 80W90 GEAR OIL		Version: 1.2
PM5831		

29 CFR 1910.1200 (OSHA HazCom 2012)

## SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

### Product identifier

Trade name : PARTS Master® 80W90  
GEAR OIL

### Recommended use of the chemical and restrictions on use


<b>Details of the supplier of the safety data sheet</b> Ashland P.O. Box 2219 Columbus, OH 43216 United States of America  EHS Customer Requests@ashland.com	<b>Emergency telephone number</b> 1-800-ASHLAND (1-800-274-5263)  <b>Regulatory Information Number</b> 1-800-325-3751  <b>Product Information</b> 614-790-3333
--	---

## SECTION 2. HAZARDS IDENTIFICATION

### GHS Classification

Skin irritation : Category 2  
 Eye irritation : Category 2A  
 Skin sensitization : Category 1

### GHS Label element

Hazard pictograms : 

Signal Word : Warning

Hazard Statements : Causes skin irritation.  
 May cause an allergic skin reaction.  
 Causes serious eye irritation.

Precautionary Statements : If medical advice is needed, have product container or label at hand.  
 Keep out of reach of children.  
 Read label before use.

### Prevention:

Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

<b>ASHLAND®</b>		Page: 2
<b>SAFETY DATA SHEET</b>		Revision Date: 06/02/2015
		Print Date: 6/11/2015
		SDS Number: R0091437
PARTS Master® 80W90 GEAR OIL		Version: 1.2
PM5831		

Wash skin thoroughly after handling.  
 Contaminated work clothing must not be allowed out of the workplace.  
 Wear eye protection/ face protection.  
 Wear protective gloves.  
**Response:**  
 IF ON SKIN: Wash with plenty of soap and water.  
 IF IN EYES: Rinse cautiously with water for several minutes.  
 Remove contact lenses, if present and easy to do. Continue rinsing.  
 If skin irritation or rash occurs: Get medical advice/ attention.  
 If eye irritation persists: Get medical advice/ attention.  
 Take off contaminated clothing and wash before reuse.  
**Disposal:**  
 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

---

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture  
 Chemical nature : Defatter

**Hazardous components**

Chemical Name	CAS-No.	Classification	Concentration (%)
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC	64742-62-7	Not a hazardous substance or mixture.	21.10
MINERAL OIL		Not a hazardous substance or mixture.	1.39
ALKYL PHOSPHATE		Skin Corr. 1B; H314  Eye Dam. 1; H318  STOT SE 3; H335	1.02
LONG-CHAIN ALKYL AMINE		Acute Tox. 4; H302  Acute Tox. 2; H330  Acute Tox. 3; H311	0.34

<b>ASHLAND®</b>		Page: 3
<b>SAFETY DATA SHEET</b>		Revision Date: 06/02/2015
		Print Date: 6/11/2015
		SDS Number: R0091437
PARTS Master® 80W90 GEAR OIL		Version: 1.2
PM5831		

		Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	
--	--	--	--

---

**SECTION 4. FIRST AID MEASURES**

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
  
- If inhaled : If breathed in, move person into fresh air.  
If unconscious place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
  
- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.  
If on skin, rinse well with water.  
Wash contaminated clothing before re-use.
  
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Protect unharmed eye.
  
- If swallowed : Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
  
- Most important symptoms and effects, both acute and delayed : Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:  
stomach or intestinal upset (nausea, vomiting, diarrhea)  
irritation (nose, throat, airways)  
Dizziness  
Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.
  
- Notes to physician : No hazards which require special first aid measures.

<b>ASHLAND®</b>		Page: 4
<b>SAFETY DATA SHEET</b>		Revision Date: 06/02/2015
		Print Date: 6/11/2015
		SDS Number: R0091437
PARTS Master® 80W90 GEAR OIL		Version: 1.2
PM5831		

---

## SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Water spray  
Foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide  
Hydrocarbons  
Oxides of phosphorus
- Specific extinguishing methods :
- Product is compatible with standard fire-fighting agents.
- Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

---

## SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.
- Other information : Comply with all applicable federal, state, and local regulations.

---

## SECTION 7. HANDLING AND STORAGE

<b>ASHLAND®</b>		Page: 5
<b>SAFETY DATA SHEET</b>		Revision Date: 06/02/2015
		Print Date: 6/11/2015
		SDS Number: R0091437
PARTS Master® 80W90 GEAR OIL		Version: 1.2
PM5831		

Advice on safe handling : Do not breathe vapours/dust.  
Do not smoke.  
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Container hazardous when empty.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
Smoking, eating and drinking should be prohibited in the application area.  
For personal protection see section 8.  
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Electrical installations / working materials must comply with the technological safety standards.

---

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC	64742-62-7	PEL	500 ppm 2,000 mg/m3	OSHA_TRANS
		REL	5 mg/m3 Mist.	NIOSH/GUIDE
		STEL	10 mg/m3 Mist.	NIOSH/GUIDE
		PEL	5 mg/m3 Mist.	OSHA_TRANS
MINERAL OIL		REL	5 mg/m3 Mist.	NIOSH/GUIDE
		STEL	10 mg/m3 Mist.	NIOSH/GUIDE
		PEL	5 mg/m3 Mist.	OSHA_TRANS
		TWA	5 mg/m3 Mist.	TN OEL
		TWA	5 mg/m3 Inhalable fraction.	ACGIH

Engineering measures : Provide sufficient mechanical (general and/or local exhaust)

<b>ASHLAND®</b>		Page: 6
<b>SAFETY DATA SHEET</b>		Revision Date: 06/02/2015
		Print Date: 6/11/2015
		SDS Number: R0091437
PARTS Master® 80W90 GEAR OIL		Version: 1.2
PM5831		

ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

#### Personal protective equipment

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Skin and body protection

: Wear as appropriate:  
impervious clothing  
Safety shoes  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.  
Discard gloves that show tears, pinholes, or signs of wear.  
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures

: Wash hands before breaks and at the end of workday.  
When using do not eat or drink.  
When using do not smoke.

---

#### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state

: liquid

Colour

: amber

Odour

: No data available

Odour Threshold

: No data available

pH

: No data available

: No data available

Boiling point/boiling range

: > 424.9 °F / 218.3 °C  
(1013.333 hPa)

Flash point

: > 432 °F / > 222 °C  
Method: Cleveland open cup

Evaporation rate

: > 1  
Ethyl Ether

Flammability (solid, gas)

: No data available

Upper explosion limit

: No data available

<b>ASHLAND®</b>		Page: 7
<b>SAFETY DATA SHEET</b>		Revision Date: 06/02/2015
		Print Date: 6/11/2015
		SDS Number: R0091437
PARTS Master® 80W90 GEAR OIL		Version: 1.2
PM5831		

Lower explosion limit : No data available

Vapour pressure : < 0.1000000 mmHg

Relative vapour density : > 1AIR=1

Relative density : 0.89 (60.00 °F)

Density : 0.8916 g/cm3 (15.56 °C)

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 146 mm2/s (40 °C)

Oxidizing properties : No data available

---

## SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Product will not undergo hazardous polymerization.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : carbon dioxide and carbon monoxide

---

## SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation  
Skin contact  
Eye Contact

<b>ASHLAND®</b>		Page: 8
<b>SAFETY DATA SHEET</b>		Revision Date: 06/02/2015
		Print Date: 6/11/2015
		SDS Number: R0091437
PARTS Master® 80W90 GEAR OIL		Version: 1.2
PM5831		

### Ingestion

**Acute toxicity**

Not classified based on available information.

**Components:**

**DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC:**

Acute oral toxicity : LD 50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l  
 Exposure time: 4 h  
 Test atmosphere: dust/mist  
 Assessment: Not classified as acutely toxic by inhalation under GHS.  
 Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD 50 (Rabbit): > 5,000 mg/kg  
 Remarks: No mortality observed at this dose.

LD 50 (Rabbit): > 2,000 mg/kg  
 Assessment: Not classified as acutely toxic by dermal absorption under GHS.

**LONG-CHAIN ALKYL AMINE:**

Acute oral toxicity :  
 Assessment: The component/mixture is classified as acute oral toxicity, category 4.

Acute inhalation toxicity : Assessment: The component/mixture is classified as acute inhalation toxicity, category 2.

Acute dermal toxicity : Assessment: The component/mixture is classified as acute dermal toxicity, category 3.

**Skin corrosion/irritation**

Causes skin irritation.

**Product:**

Remarks: May cause skin irritation and/or dermatitis.

Result: Repeated exposure may cause skin dryness or cracking.

**Components:**

**DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC:**

Species: Rabbit

Result: Not irritating to skin

**MINERAL OIL:**

Result: Mildly irritating to skin

**ALKYL PHOSPHATE:**

Result: Corrosive to skin

**LONG-CHAIN ALKYL AMINE:**

Result: Corrosive after 3 minutes to 1 hour of exposure



<b>ASHLAND®</b>		Page: 9
<b>SAFETY DATA SHEET</b>		Revision Date: 06/02/2015
		Print Date: 6/11/2015
		SDS Number: R0091437
PARTS Master® 80W90 GEAR OIL		Version: 1.2
PM5831		

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Product:**

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.

**Components:**

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC:

Species: Rabbit

Result: Not irritating to eyes

MINERAL OIL:

Result: Mildly irritating to eyes

ALKYL PHOSPHATE:

Result: Corrosive to eyes

LONG-CHAIN ALKYL AMINE:

Result: Corrosive to eyes

**Respiratory or skin sensitisation**

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

**Components:**

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC:

Test Type: Buehler Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

LONG-CHAIN ALKYL AMINE:

Assessment: May cause sensitisation by skin contact.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

Not classified based on available information.

**Components:**

ALKYL PHOSPHATE:

Assessment: May cause respiratory irritation.

**STOT - repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**Product:**

No aspiration toxicity classification

**Components:**

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC:

<b>ASHLAND®</b>		Page: 10
<b>SAFETY DATA SHEET</b>		Revision Date: 06/02/2015
		Print Date: 6/11/2015
		SDS Number: R0091437
PARTS Master® 80W90 GEAR OIL		Version: 1.2
PM5831		

No aspiration toxicity classification

**Further information**

**Product:**

Remarks: No data available

**Carcinogenicity:**

**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

---

**SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

**Components:**

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
 Exposure time: 96 h  
 Test Type: static test  
 Test substance: WAF  
 Method: OECD Test Guideline 203  
 Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l  
 Exposure time: 48 h  
 Test Type: static test  
 Test substance: WAF  
 Method: OECD Test Guideline 202

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l  
 End point: Growth inhibition  
 Exposure time: 72 h  
 Test Type: static test  
 Test substance: WAF  
 Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOELR (Oncorhynchus mykiss (rainbow trout)): Calculated >= 1,000 mg/l  
 Exposure time: 14 d

Toxicity to daphnia and other : NOEL (Daphnia (water flea)): 10 mg/l

<b>ASHLAND®</b>		Page: 11
<b>SAFETY DATA SHEET</b>		Revision Date: 06/02/2015
		Print Date: 6/11/2015
		SDS Number: R0091437
PARTS Master® 80W90 GEAR OIL		Version: 1.2
PM5831		

aquatic invertebrates  
(Chronic toxicity)

Exposure time: 21 d  
Test substance: WAF  
Method: OECD Test Guideline 211

LONG-CHAIN ALKYL AMINE:  
Ecotoxicology Assessment  
Acute aquatic toxicity

: Very toxic to aquatic life.

Chronic aquatic toxicity

: Very toxic to aquatic life with long lasting effects.

#### **Persistence and degradability**

##### **Components:**

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC:

Biodegradability

: Result: Not readily biodegradable.  
Biodegradation: 2 - 4 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

#### **Bioaccumulative potential**

##### **Components:**

No data available

##### **Mobility in soil**

##### **Components:**

No data available

##### **Other adverse effects**

No data available

##### **Product:**

Additional ecological  
information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

##### **Components:**

## **SECTION 13. DISPOSAL CONSIDERATIONS**

#### **Disposal methods**

General advice

: The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging

: Empty remaining contents.  
Dispose of as unused product.  
Empty containers should be taken to an approved waste

**SAFETY DATA SHEET**

Revision Date: 06/02/2015

Print Date: 6/11/2015

SDS Number: R0091437

PARTS Master® 80W90 GEAR OIL

Version: 1.2

PM5831

handling site for recycling or disposal.  
Do not re-use empty containers.

**SECTION 14. TRANSPORT INFORMATION****International transport regulations****REGULATION**

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

**U.S. DOT - ROAD**

Not dangerous goods

**U.S. DOT - RAIL**

Not dangerous goods

**U.S. DOT - INLAND WATERWAYS**

Not dangerous goods

**TRANSPORT CANADA - ROAD**

Not dangerous goods

**TRANSPORT CANADA - RAIL**

Not dangerous goods

**TRANSPORT CANADA - INLAND WATERWAYS**

Not dangerous goods

**INTERNATIONAL MARITIME DANGEROUS GOODS**

Not dangerous goods

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO**

Not dangerous goods

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER**

Not dangerous goods

**MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES**

Not dangerous goods

<b>ASHLAND®</b>		Page: 13
<b>SAFETY DATA SHEET</b>		Revision Date: 06/02/2015
		Print Date: 6/11/2015
		SDS Number: R0091437
PARTS Master® 80W90 GEAR OIL		Version: 1.2
PM5831		

\*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

## SECTION 15. REGULATORY INFORMATION

**SARA 311/312 Hazards** : Acute Health Hazard

**SARA 313 Component(s)SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

### Pennsylvania Right To Know

HEAVY PARAFFINIC DISTILLATE	64742-54-7	70.00 - 90.00 %
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC	64742-62-7	20.00 - 30.00 %
LUBRICANT ADDITIVE	Not Assigned	5.00 - 10.00 %

### New Jersey Right To Know

HEAVY PARAFFINIC DISTILLATE	64742-54-7	70.00 - 90.00 %
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC	64742-62-7	20.00 - 30.00 %
LUBRICANT ADDITIVE	Not Assigned	5.00 - 10.00 %
MINERAL OIL	Not Assigned	1.00 - 5.00 %
ALKYL PHOSPHATE	Not Assigned	1.00 - 5.00 %
DISTILLATES (PETROLEUM), SOLVENT- DEWAXED HEAVY PARAFFINIC	64742-65-0	0.10 - 1.00 %

**California Prop 65** : Proposition 65 warnings are not required for this product based on the results of a risk assessment.

**The components of this product are reported in the following inventories:**

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL.

AUSTR : On the inventory, or in compliance with the inventory

<b>ASHLAND®</b>		Page: 14
<b>SAFETY DATA SHEET</b>		Revision Date: 06/02/2015
		Print Date: 6/11/2015
		SDS Number: R0091437
PARTS Master® 80W90 GEAR OIL		Version: 1.2
PM5831		

- ENCS : On the inventory, or in compliance with the inventory
- KECL : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory

**Inventories**

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECL (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

**SECTION 16. OTHER INFORMATION**

**Further information**

Revision Date: 06/02/2015

<b>NFPA:</b>	<b>HMIS III:</b>						
<p>Flammability</p> <p>Health: 1, Flammability: 1, Instability: 0, Special hazard.</p>	<table border="1"> <tr> <td><b>HEALTH</b></td> <td><b>1</b></td> </tr> <tr> <td><b>FLAMMABILITY</b></td> <td><b>1</b></td> </tr> <tr> <td><b>PHYSICAL HAZARD</b></td> <td><b>0</b></td> </tr> </table> <p>0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	<b>HEALTH</b>	<b>1</b>	<b>FLAMMABILITY</b>	<b>1</b>	<b>PHYSICAL HAZARD</b>	<b>0</b>
<b>HEALTH</b>	<b>1</b>						
<b>FLAMMABILITY</b>	<b>1</b>						
<b>PHYSICAL HAZARD</b>	<b>0</b>						

**NFPA Flammable and Combustible Liquids Classification**  
Combustible Liquid Class IIIB

**Full text of H-Statements referred to under sections 2 and 3.**

- H302 Harmful if swallowed.
- H311 Toxic in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H330 Fatal if inhaled.
- H335 May cause respiratory irritation.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

**Further information**

<b>ASHLAND®</b>		Page: 15
<b>SAFETY DATA SHEET</b>		Revision Date: 06/02/2015
		Print Date: 6/11/2015
		SDS Number: R0091437
PARTS Master® 80W90 GEAR OIL		Version: 1.2
PM5831		

Sources of key data used to compile the Safety Data Sheet  
Ashland internal data including own and sponsored test reports  
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists  
BEI : Biological Exposure Index  
CAS : Chemical Abstracts Service (Division of the American Chemical Society).  
CMR : Carcinogenic, Mutagenic or Toxic for Reproduction  
FG : Food grade  
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.  
H-statement : Hazard Statement  
IATA : International Air Transport Association.  
IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization  
ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"  
IMDG : International Maritime Code for Dangerous Goods  
ISO : International Organization for Standardization  
logPow : octanol-water partition coefficient  
LCxx : Lethal Concentration, for xx percent of test population  
LDxx : Lethal Dose, for xx percent of test population.  
ICxx : Inhibitory Concentration for xx of a substance  
Ecxx : Effective Concentration of xx  
N.O.S.: Not Otherwise Specified  
OECD : Organization for Economic Co-operation and Development  
OEL : Occupational Exposure Limit  
P-Statement : Precautionary Statement  
PBT : Persistent , Bioaccumulative and Toxic  
PPE : Personal Protective Equipment  
STEL : Short-term exposure limit  
STOT : Specific Target Organ Toxicity  
TLV : Threshold Limit Value  
TWA : Time-weighted average  
vPvB : Very Persistent and Very Bioaccumulative  
WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act  
DOT : Department of Transportation  
FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act  
HMIRC : Hazardous Materials Information Review Commission  
HMIS : Hazardous Materials Identification System  
NFPA : National Fire Protection Association  
NIOSH : National Institute for Occupational Safety and Health

<b>ASHLAND®</b>		Page: 16
<b>SAFETY DATA SHEET</b>		Revision Date: 06/02/2015
		Print Date: 6/11/2015
		SDS Number: R0091437
PARTS Master® 80W90 GEAR OIL		Version: 1.2
PM5831		

OSHA : Occupational Safety and Health Administration  
 PMRA : Health Canada Pest Management Regulatory Agency  
 RTK : Right to Know  
 WHMIS : Workplace Hazardous Materials Information System